



### Main

Range	Vivace
Device short name	KB31
Product or component type	Dimmer
Device presentation	Complete mechanism
Colour tint	White

### Complementary

Power range	Tungsten filament: 400 W
[Ue] rated operational voltage	220...240 V AC
Network frequency	50 Hz
Number of gangs	1 gang
Connections - terminals	Pillar terminals
Terminal identifier	L Load
Tightening torque	0.4 N.m
Clamping connection capacity	1.5 mm <sup>2</sup>
Contacts material	Brass and phosphor bronze
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Width	87 mm
Height	87 mm
Projecting depth	8 mm
Embedding depth	35 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	IEC 60669-2-1

## Packing Units

Package 1 Weight	93.600 g
Package 1 Height	1.000 mm
Package 1 width	1.000 mm
Package 1 Length	1.000 mm